

- 3196 Thompson Rd Fenton, MI 48430
- **&** 810-629-9558
- (i) defender@thompsonig.com

## **PRODUCT SPECIFICATION SHEET**

## **Thompson DEFENDER**



PRODUCT	Bullet Resistant Glass Clad No-Poly; Level 3 - Low Spall
Part ID	BR-GCNP-L3
Performance Testing	BALLISTIC RATING UL 752 Level 3 (Modified for Low Spall)  • No Penetration / Low Spall  • .44 Magnum Pistol, 3 shots  • Witness Plate @ 18"  • NTS-BR-PH00008978  FORCED ENTRY RATING ASTM F1233-08 Standard Test for Security Glazing Materials  • Class Achieved 1.3  • NTS-FE-PH00008737
Construction	Proprietary Layers     Glass on both exposed surfaces
Thickness	1 1/4"
Thickness Tolerance	±1/16"
Weight	14.47 lbs./sq. ft.
Size	Minimum: 9" x 15" Maximum: 72" x 140"
Options	Tints Bird-Friendly Low-E Low Iron Mirropane (Please contact us for more options)
Warranty	Five (5) Years from date of manufacture. For more information, please visit www.thompsonig.com/resources
Compliance	ASTM – C1036 – Standard Specifications for Flat Glass ASTM - C1349 - Standard Specification for Architectural Flat Glass Clad Polycarbonate ANSI Z97.1: Safety Materials Used in Buildings