



📍 3196 Thompson Rd
Fenton, MI 48430

📞 810-629-9558

📧 defender@thompsonig.com

PRODUCT SPECIFICATION SHEET

Thompson DEFENDER



PRODUCT	Bullet Resistant Glass Clad (1.125"); Level 3 - Low Spall
Part ID	BR-GC-L3-1.125
Performance Testing	<p>BALLISTIC RATING</p> <p>UL 752 Level 3 (Modified for Low Spall)</p> <ul style="list-style-type: none">• No Penetration / Low Spall• .44 Magnum Pistol, 3 shots• Witness Plate @ 6"• NTS-BR-PR158089 <p>FORCED ENTRY RATING</p> <p>ASTM F1233-08 Standard Test for Security Glazing Materials</p> <ul style="list-style-type: none">• Class Achieved 1.4• NTS-FE-PH00008160R2
Construction	<ul style="list-style-type: none">• Proprietary Layers• Glass on both exposed surfaces
Thickness	1 1/8"
Thickness Tolerance	±1/16"
Weight	13.39 lbs./sq. ft.
Size	Minimum: 9" x 15" Maximum: 72" x 130"
Options	Please contact us for glass options
Warranty	Five (5) Years from date of manufacture. For more information, please visit www.thompsonig.com/resources
Compliance	ASTM - C1036 - Standard Specifications for Flat Glass ASTM - C1349 - Standard Specification for Architectural Flat Glass Clad Polycarbonate ANSI Z97.1: Safety Materials Used in Buildings