



📍 3196 Thompson Rd
Fenton, MI 48430

📞 810-629-9558

📧 defender@thompsonig.com

PRODUCT SPECIFICATION SHEET

Thompson DEFENDER



PRODUCT	Forced Entry Monolithic Laminate; Class 1.3
Part ID	FE-MONO-1.3
Performance Testing	<p>FORCED ENTRY RATING</p> <p>ASTM F1233-08 Standard Test for Security Glazing Materials</p> <ul style="list-style-type: none">• Class Achieved 1.3• PH4815 <p>UL 972-2006 Standard for Burglary Resistant Glazing Material</p> <ul style="list-style-type: none">• S4804.01-109-44
Construction	<ul style="list-style-type: none">• Proprietary Layers• Glass on both exposed surfaces
Thickness	3/8"
Thickness Tolerance	±1/16"
Weight	4.1 lbs./sq. ft.
Size	Minimum: 9" x 15" Maximum: 72" x 140"
Options	Insulated Glass Units (1.00" - 1.50") Tints Bird-Friendly Low-E Low Iron (Please contact us for more options)
Warranty	Five (5) Years from date of manufacture. For more information, please visit www.thompsonig.com/resources
Compliance	ASTM – C1036 – Standard Specifications for Flat Glass ANSI Z97.1: Safety Materials Used in Buildings