



📍 3196 Thompson Rd  
Fenton, MI 48430

📞 810-629-9558

📧 defender@thompsonig.com

## PRODUCT SPECIFICATION SHEET

# Thompson DEFENDER



PRODUCT	Forced Entry Monolithic Laminate; Class 2.0
Part ID	FE-MONO-2.0
Performance Testing	FORCED ENTRY RATING  ASTM F1233-08 Standard Test for Security Glazing Materials • Class Achieved 2.0 • NTS-FE-PH00015605
Construction	• Proprietary Layers • Glass on both exposed surfaces
Thickness	7/16"
Thickness Tolerance	±1/16"
Weight	4.55 lbs./sq. ft.
Size	Minimum: 9" x 15" Maximum: 72" x 130"
Options	Insulated Glass Units (1.00" - 1.50") Tints Bird-Friendly Low-E Low Iron (Please contact us for more options)
Warranty	Five (5) Years from date of manufacture. For more information, please visit <a href="http://www.thompsonig.com/resources">www.thompsonig.com/resources</a>
Compliance	ASTM – C1036 – Standard Specifications for Flat Glass ASTM - C1349 - Standard Specification for Architectural Flat Glass Clad Polycarbonate ANSI Z97.1: Safety Materials Used in Buildings