



📍 3196 Thompson Rd
Fenton, MI 48430

📞 810-629-9558

📧 defender@thompsonig.com

PRODUCT SPECIFICATION SHEET

Thompson DEFENDER



PRODUCT	Bullet Resistant Glass Clad No-Poly; Level 3 - Low Spall
Part ID	BR-GCNP-L3
Performance Testing	BALLISTIC RATING UL 752 Level 3 (Modified for Low Spall) • No Penetration / Low Spall • .44 Magnum Pistol, 3 shots • NTS-BR-PH00008978 FORCED ENTRY RATING ASTM F1233-08 Standard Test for Security Glazing Materials • Class Achieved 1.3 • NTS-FE-PH00008737
Construction	• Proprietary Layers • Glass on both exposed surfaces
Thickness	1 1/4"
Thickness Tolerance	±1/16"
Weight	14.47 lbs./sq. ft.
Size	Minimum: 9" x 15" Maximum: 72" x 140"
Options	Tints Bird-Friendly Low-E Low Iron Mirropane (Please contact us for more options)
Warranty	Five (5) Years from date of manufacture. For more information, please visit www.thompsonig.com/resources
Compliance	ASTM – C1036 – Standard Specifications for Flat Glass ASTM - C1349 - Standard Specification for Architectural Flat Glass Clad Polycarbonate ANSI Z97.1: Safety Materials Used in Buildings