

- 3196 Thompson Rd Fenton, MI 48430
- **&** 810-629-9558
- i defender@thompsonig.com

PRODUCT SPECIFICATION SHEET

Thompson DEFENDER



PRODUCT	Bullet Resistant Insulated Glass Unit (IGU) No-Poly Level 1 - Low Spall
Part ID	BR-IGUNP-L1
Performance Testing	BALLISTIC RATING UL 752 Level 1 (Modified for Low Spall) • No Penetration / Low Spall • 9mm Pistol, 3 shots • NTS-BR-PH00009178 FORCED ENTRY RATING ASTM F1233-08 Standard Test for Security Glazing Materials • Class Achieved 1.3 • Intertek FE-L0053.01-119-12RO
Construction	Proprietary Layers Glass on both exposed surfaces
Thickness	1 1/8"
Thickness Tolerance	±1/16"
Weight	7.61 lbs./sq. ft.
Size	Minimum: 9" x 15" Maximum: 72" x 140"
Options	Tints Bird-Friendly Low-E Low Iron (Please contact us for more options)
Warranty	Five (5) Years from date of manufacture. For more information, please visit www.thompsonig.com/resources
Compliance	ASTM – C1036 – Standard Specifications for Flat Glass ANSI Z97.1: Safety Materials Used in Buildings