



3196 Thompson Rd
Fenton, MI 48430

810-629-9558

defender@thompsonig.com

PRODUCT SPECIFICATION SHEET

Thompson DEFENDER



| PRODUCT | Bullet Resistant Glass Clad; Level 5 - Low Spall |
|---------------------|--|
| Part ID | BR-GC-L5 |
| Performance Testing | <p>BALLISTIC RATING UL 752 Level 5 (Modified for Low Spall)</p> <ul style="list-style-type: none"> • No Penetration / Low Spall • 7.62mm Rifle, 1 shot • NTS-BR-PH000005750A <p>FORCED ENTRY RATING ASTM F1233-08 Standard Test for Security Glazing Materials</p> <ul style="list-style-type: none"> • Class Achieved 2.0 • PH00010308-B |
| Construction | <ul style="list-style-type: none"> • Proprietary Layers • Glass on both exposed surfaces |
| Thickness | 1 9/16" |
| Thickness Tolerance | ±3/32" |
| Weight | 17.95 lbs./sq. ft. |
| Size | Minimum: 9" x 15" Maximum: 72' x 130" |
| Options | Please contact us for glass options |
| Warranty | Five (5) Years from date of manufacture. For more information, please visit www.thompsonig.com/resources |
| Compliance | ASTM – C1036 – Standard Specifications for Flat Glass ASTM - C1349 - Standard Specification for Architectural Flat Glass Clad Polycarbonate ANSI Z97.1: Safety Materials Used in Buildings |