



📍 3196 Thompson Rd
Fenton, MI 48430

📞 810-629-9558

📧 defender@thompsonig.com

PRODUCT SPECIFICATION SHEET

Thompson DEFENDER



PRODUCT	Bullet Resistant Glass Clad; Level 5 - Low Spall
Part ID	BR-GC-L5
Performance Testing	<p>BALLISTIC RATING UL 752 Level 5 (Modified for Low Spall)</p> <ul style="list-style-type: none"> • No Penetration / Low Spall • 7.62mm Rifle, 1 shot • NTS-BR-PH000005750A <p>FORCED ENTRY RATING ASTM F1233-08 Standard Test for Security Glazing Materials</p> <ul style="list-style-type: none"> • Class Achieved 2.0 • PH00010308-B
Construction	<ul style="list-style-type: none"> • Proprietary Layers • Glass on both exposed surfaces
Thickness	1 9/16"
Thickness Tolerance	±3/32"
Weight	17.95 lbs./sq. ft.
Size	Minimum: 9" x 15" Maximum: 72" x 130"
Options	Please contact us for glass options
Warranty	Five (5) Years from date of manufacture. For more information, please visit www.thompsonig.com/resources
Compliance	ASTM – C1036 – Standard Specifications for Flat Glass ASTM - C1349 - Standard Specification for Architectural Flat Glass Clad Polycarbonate ANSI Z97.1: Safety Materials Used in Buildings